


Figure 1

Koved et al.
AUS920010941US1
Method and Apparatus for Type
Independent Permission Based
Access Control
Page 1 of 13






Figure 2




Figure 3

Koved et al.
AUS920010941US1
Method and Apparatus for Type
Independent Permission Based
Access Control
Page 3 of 13




Figure 4




Figure 5

Koved et al.
AUS920010941US1
Method and Apparatus for Type
Independent Permission Based
Access Control
Page 5 of 13

US 2004/0183111 A1
Koved et al.
Method and Apparatus for Type
Independent Permission Based
Access Control
Page 6 of 12




Figure 6

```

import java.security.BasicPermission;
import java.security.Permission;
import java.security.PermissionCollection;
import java.util.Hashtable;
import java.util.Enumeration;

public class IBMPermission extends BasicPermission
{
    public IBMPermission()
    {
        super("");
        System.out.println("Constructor IBMPermission() called");
    }
    public IBMPermission(String target)
    {
        super(target);
        System.out.println("Constructor IBMPermission(target) called");
    }
    public IBMPermission(String target, String actions)
    {
        super(target, actions);
        System.out.println("Constructor IBMPermission(target, actions) called");
    }
    public boolean implies(Permission perm)
    {
        System.out.println("IBMPermission.implies() called");

        if (perm instanceof IBMPermission)
            return true;
        return false;
    }
    public PermissionCollection newPermissionCollection()
    {
        return new IBMPermissionCollection();
    }
}

```

Figure 7A

Koved et al.
 AUS920010941US1
 Method and Apparatus for Type
 Independent Permission Based
 Access Control
 Page 7 of 13

```

final class IBMPermissionCollection extends PermissionCollection
    implements java.io.Serializable
{
    private Hashtable permissions;

    public IBMPermissionCollection()
    {
        permissions = new Hashtable();
    }

    public void add(Permission permission)
    {
        if (! (permission instanceof IBMPermission))
            throw new IllegalArgumentException("Invalid Permission: " +
                                             permission);

        IBMPermission ibmp = (IBMPermission) permission;
        permissions.put(ibmp.getName(), permission);
    }

    public boolean implies(Permission permission)
    {
        if (! (permission instanceof IBMPermission))
            return false;

        System.out.println("permission instanceof IBMPermission == true");

        IBMPermission ibmp = (IBMPermission) permission;
        String permName = ibmp.getName();
        Permission x = (Permission) permissions.get(permName);

        if (x != null)
        {
            System.out.println("We have a direct hit! " + x.getName());
            return x.implies(permission);
        }

        Enumeration permEnum = permissions.elements();

        while (permEnum.hasMoreElements())
        {
            x = (IBMPermission) permEnum.nextElement();
            System.out.println(x.getName());

            if (x.implies(permission))
                return true;
        }

        return false;
    }

    public Enumeration elements()
    {
        return permissions.elements();
    }
}

```

Figure 7B

Koved et al.
 AUS920010941US1
 Method and Apparatus for Type
 Independent Permission Based
 Access Control
 Page 8 of 13


```

import java.security.PermissionCollection;
import java.security.AccessController;
import java.security.AccessControlContext;
import java.security.AccessControlException;

public class WSPermission extends IBMPermission
{
    public WSPermission(String target)
    {
        super(target);
        System.out.println("Constructor WSPermission(target) called");
    }

    public WSPermission(String target, String actions)
    {
        super(target, actions);
        System.out.println("Constructor WSPermission(target, actions) called");
    }

    public WSPermission()
    {
        super("");
        System.out.println("Constructor WSPermission() called");
    }

    /**
     * Returns a new IBMPermissionCollection object for storing IBMPermission
     * objects.
     * <p>
     * An IBMPermissionCollection stores a collection of
     * IBMPermission permissions.
     * <p>
     * IBMPermission objects must be stored in a manner that allows them
     * to be inserted in any order, but that also enables the
     * PermissionCollection <code>implies</code> method
     * to be implemented in an efficient (and consistent) manner.
     *
     * @return a new IBMPermissionCollection object suitable for
     *         storing IBMPermission's.
     */
    public PermissionCollection newPermissionCollection()
    {
        System.out.println("newPermissionCollection() was called");
        IBMPermissionCollection ibmPC = new IBMPermissionCollection();

        // the code here checks if an IBMPermissionCollection has been granted.
        // If yes, then the PermissionCollection returned by this
        // method should contain a WSPermission.

        AccessControlContext acc = AccessController.getContext();

        try
        {
            acc.checkPermission(new IBMPermission("PermissionTest"));
            ibmPC.add(new WSPermission("PermissionTest"));
        }
        catch (AccessControlException ace)
        {
            System.out.println("IBMPermission WAS NOT GRANTED");
        }
        return ibmPC;
    }
}

```

Figure 7C

Koved et al.
 AUS920010941US1
 Method and Apparatus for Type
 Independent Permission Based
 Access Control
 Page 9 of 13

```

import java.io.*;

public class PermissionTest
{
    public static void main(String args[])
    {
        try
        {
            SecurityManager sm = System.getSecurityManager();

            if (sm != null)
            {
                System.out.println("SecurityManager is checking for " +
                                   "WSPermission");

                sm.checkPermission(new WSPermission("PermissionTest"));
            }

            System.out.println("WSPermission was granted. " +
                               "Permission testing
worked.\n\n\n");

            File inputFile = new File("C:\\winzip.log");
            FileInputStream fis = new FileInputStream(inputFile);
            InputStreamReader isr = new InputStreamReader(fis);
            BufferedReader br = new BufferedReader(isr);

            String lineRead;
            while ((lineRead = br.readLine()) != null)
                System.out.println(lineRead);
        }

        catch(Exception e)
        {
            e.printStackTrace();
        }
    }
}

```

Figure 8

Koved et al.
 AUS920010941US1
 Method and Apparatus for Type
 Independent Permission Based
 Access Control
 Page 10 of 13




Figure 9

Koved et al.
 AUS920010941US1
 Method and Apparatus for Type
 Independent Permission Based
 Access Control
 Page 11 of 13

FIG. 9 is a flowchart illustrating a method for determining whether a resource access request should be granted or denied based on a permission-based access control system. The method starts at a "Start" block, proceeds to a block labeled "Recieve Untrusted Resource Access Request 910", then to a block labeled "Determine Required Permission based on CodeSource and Resource 920". From there, the method proceeds to a block labeled "Call SecurityManager Check Permission on the Permission 930", then to a block labeled "Call AccessControlContext Check Permission on AccessControlContext 940", then to a block labeled "Call implies() Method on Protection Domain 950", then to a block labeled "Call new Permission Collection 960". The method then reaches a decision diamond labeled "Superclass Permission Present in All Protection Domains in Stack? 970". If the answer is "NO", the method proceeds to a block labeled "Deny Resource Access Request 975". If the answer is "YES", the method proceeds to a block labeled "Add Permission to Permission Collection 980", then to a block labeled "Add Any Subclass Permissions to Permission Collection 985" (which is shown in a dashed box), then to a block labeled "Add Permission Collection to AccessControlContext 990", then to a block labeled "Grant Resource Access Request 995". Both the "Deny Resource Access Request 975" block and the "Grant Resource Access Request 995" block lead to an "End" block.




Figure 10

Koved et al.
AUS920010941US1
Method and Apparatus for Type
Independent Permission Based
Access Control
Page 12 of 13

```

package sun.security.provider;

import java.security.PermissionCollection;
import java.security.CodeSource;
import IBMPermission;
import WSPermission;

public class MarcoPolicy extends PolicyFile
{
    public PermissionCollection getPermissions(CodeSource codesource)
    {
        PermissionCollection pc = super.getPermissions(codesource);

        if (pc == null)
            return null;

        if (pc.implies(new IBMPermission("PermissionTest")))
            pc.add(new WSPermission("PermissionTest"));

        return pc;
    }
}

```

Figure 11

Koved et al.
 AUS920010941US1
 Method and Apparatus for Type
 Independent Permission Based
 Access Control
 Page 13 of 13